

MGS105

Mitre saws



The universal saw for special applications

- The reliable elumatec principle "Cutting from below":
- Free access to the table surface for optimal loading and unloading of profiles
- The patented saw arm suspension creates a cutting pressure towards the back fence which ensures safe clamping of the workpiece
- Safety hood opens automatically
- Pulsed coolant system
- Equipped with saw blade as standard

Options

- Extraction system
- Length stop and measuring systems
- Roller conveyors
- Saw blades
- High performance cutting fluid




Mitre saw MGS 105



Mitre saw MGS 105



Mitre saw MGS 105



Mitre saw MGS 105

Cutting diagram MGS 105

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.

MGS 105 / MITRE SAWS

- Pivoting range manually 22.5° to the left and right with digital display E111
- Tilting range pneumatically from 90° - 45°
- For cutting range, see cutting diagram
- Saw blade diameter 420 mm
- Saw blade speed 2,800 rpm
- Power supply 230/400 V, 3~, 50 Hz
- Power output 4 kW
- Compressed air supply 7 bar
- Air consumption per working cycle 20 l without spraying, 32 l with spraying
- Length 1,400 mm, depth 1,500 mm, height 1,880 mm, weight 750 kg