

TECHNICAL SHEET

15/09/2025



Profile trolley for vertical storage and transportation of aluminium profiles

- Stable steel construction
- Ideal for transportation and space-saving intermediate storage of cut-to-length profiles
- Vertical profile transportation
- Sufficient for 12 60 profile bars
- Compartment divider height is adjustable
- Lower supporting surface with rubber strips
- Compartment dividers with protective tubing
- Rear back support with rubber strips
- Four castors, two of which have a fixing brake

Options


• Height of additional compartment divider is adjustable, with plastic protector

1

elumatec

TECHNICAL SHEET

15/09/2025



Profile transport trolley PWS 1800



Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling




Compartment divider with plastic protector

Compartment divider height is adjustable. All supporting surfaces have a non-slip PVC cladding which protects surfaces from damage during storage



Back support with rubber strips

Rear supporting surfaces equipped with rubber strips protect profiles from damage



Lower supporting surfaces with rubber strips

Lower supporting surfaces equipped with rubber strips to protect the profiles from damage



Additional compartment divider for PWS 1800

Additional compartment divider with height adjustment and plastic protector



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



TECHNICAL SHEET

15/09/2025

PWS 1800 / PROFILE TRANSPORT TROLLEYS

- Length 1,880 mm
- Width 800 mm
- Height 1,700 mm
- Two compartment dividers
- Twelve compartments
- Roller diameter 125 mm
- Compartment width 120 mm
- Compartment depth 540 mm
- Unit height 1,500 mm
- Weight 105 kg
- Load 350 kg

Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.