SA 142

AUTOMATIC SAWS



- Suitable for high-volume cutting of aluminium profiles for window manufacturing and industrial applications
- Material infeed (cycling) protects the surface of the workpiece through a profile lifting system at the bearing and locating face
- One, two or three-stroke feed can be selected using a selector switch
- Angled cuts of up to 45° are possible by tilting the saw unit (option)
- Large cutting range for wide profiles
- Equipped with saw blade as standard

Options

- Manual cutting length adjustment with digital display E 111
- Hydro-pneumatic saw feed
- Extraction unit
- Roller conveyors
- Saw blades
- High performance cutting fluid
- Intermediate angle setting by hand wheel and digital display E 111
- Clamping method for multi-part clamping
- Clamping method for parts smaller than 5 mm

AUTOMATIC SAW SA 142/38

See SA 142/37, however:

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.

- With kerf spreading (only for 90° cuts)
- For cutting range, see cutting diagram


elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.



Automatic saw SA 142/37




Automatic saw SA 142/37




Automatic saw SA 142/38



Automatic saw SA 142/37



Automatic saw SA 142/38




Automatic saw SA 142/37

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.



Automatic saw SA 142/37

Cutting diagram SA 142/37

elumatec AG
Pinacher Straße, 61
75417 Mühlacker
Germany

Tel +49 7041-14-184
sales@elumatec.com
www.elumatec.com

The right to make technical alterations is reserved.