

KS101/30

Vee-notch and notching
saws



- Precision Vee-cuts in aluminium and PVC profiles
- Pneumatic continuously adjustable saw blade feed for fast and precise sawing with rapid return
- Simple setting of cutting depth
- Equipped with connection for swarf extraction hose and swarf container as standard
- Equipped with saw blades as standard
- Equipped with pulsed coolant system as standard

Options

- Material clamping units
- Length stop and measuring systems
- Roller conveyor
- Saw blades
- High performance cutting fluid



Vee-notch and notching saw KS 101/30



Vee-notch and notching saw KS 101/30




Vee-notch and notching saw KS 101/30



Vee-notch and notching saw KS 101/30



Vee-notch and notching saw KS 101/30



Vee-notch and notching saw KS 101/30

Cutting diagram KS 101/30

KS 101/30 / VEE-NOTCH AND NOTCHING SAWS

- Cutting range for Vee-cuts: cutting depth 80 mm, profile height 100 mm
- Saw blade diameter 300 mm
- Saw blade speed 2,800 rpm
- Power supply 230/400 V, 3~, 50 Hz
- Power output per motor 0.9 kW
- Compressed air supply 7 bar
- Air consumption per working cycle 20 l without spraying, 44 l with spraying
- Length 980 mm, depth 800 mm, height 1,650 mm, weight 240 kg