

TECHNICAL SHEET

15/08/2025



- Profile trolley for horizontal storage and transportation of profiles
- Stable steel construction
- Horizontal profile transportation
- Profile trolley with profile supports on both sides
- Twelve storage areas per upright
- Four castors, two of which have a fixing brake

Options


- Plastic protector for PHW 1600/2000
- Number label for PHW 1600/2000

1




TECHNICAL SHEET

15/08/2025



Profile transport trolley PHW 2000



Support arms

Compartment width 120 mm, Compartment depth 450 mm, easy loading and unloading, well-organised storage provides quick access




Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



Plastic protector for PHW 1600/2000

All supporting surfaces have a non-slip PVC cladding which protects surfaces from damage during storage



Number labels for PHW 1600/2000

Numbering of the compartments PHW 1600/2000



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



TECHNICAL SHEET

15/08/2025

PHW 2000 / PROFILE TRANSPORT TROLLEYS

- Length 2,000 mm
- Width 1,000 mm
- Height 1,850 mm
- 24 shelves
- Clearance 120 mm
- Compartment width 450 mm
- Weight 150 kg
- Load 350 kg
- Roller diameter 125 mm

Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.