


TECHNICAL SHEET

25/11/2025



Profile trolley for horizontal storage and transportation of profiles

- Stable steel construction
- Horizontal profile transportation
- Support arms are rubber coated
- Profile trolley with profile supports on both sides
- Six supports per upright
- Two centre uprights
- Four castors, two of which have a fixing brake

Options

• Individual centre upright




TECHNICAL SHEET

25/11/2025



Profile transport trolley PWW 2000



Easy loading and unloading

Well-organised storage provides quick access




Support arms

Support arms are rubber coated.Adjustable centre upright



Casters

Four casters, two of which have a fixing brake, provide a high degree of mobility and easy, safe handling



Individual centre upright

Additional centre uprights



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



TECHNICAL SHEET

25/11/2025

PWW 2000 / PROFILE TRANSPORT TROLLEYS

- Length 2,000 mm
- Width 900 mm
- Height 1,960 mm
- Eleven shelves
- Clearance 260 mm
- Lower shelf width 420 mm
- Upper shelf width 300 mm
- Weight 75 kg
- Load 350 kg
- Roller diameter 125 mm

Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.