

## **TECHNICAL SHEET**

25/11/2025



Vertical roller conveyor for transportation of window elements

- Stable steel construction
- Vertical roller conveyor for smooth transportation to the next work task as well as for transportation to storage and sorting of the finished windows
- Easy handling of window elements
- Every roller conveyor unit is 3,000 mm long
- Plastic slide bars top and bottom
- Three mini-roller conveyors with rubber rollers, diameter 50 mm
- Basic unit with end rack
- Vertical roller conveyor on rails with flanged rollers, mobile

#### **Options**

- Rail, 2.0 m, left and right
- End stop for VR
- Lead-in roller for VR
- Profile protectors for support rollers (Alum.)

elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com

The right to make technical alterations is reserved.

1



## **TECHNICAL SHEET**

25/11/2025




Vertical roller conveyor VR 3003 F



**Support rollers** 

Rollers throughout, Roller conveyor divided into three parts, 3x 120 mm. Roller conveyor units, 2,000 mm, 3,000 mm and 4,000 mm long



Mini-roller conveyor

Three mini-roller conveyors with rubber rollers, diameter 50 mm



**Back support** 

Rear back support with plastic slide bars, top and bottom



#### Grip

Grip makes pushing the roller conveyor on the rails easy



#### **Mobility unit**

Mobility unit with flanged rollers and fixing brake




elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.

# elumatec

## **TECHNICAL SHEET**

25/11/2025




**End stop** 

End stop Rb = 3x 120 mm



Lead-in rollers

Protective rollers for beginning or end of roller conveyor L = 500 mm (pair) L = 250 mm (pair)



**Profile protectors** 

Profile protectors for support rollers  $3x\ 120$  mm (Alum./33 x and Alum./48 x). Support rollers covered with protective tubing



## Additional mini-roller conveyors

Additional mini-roller conveyors with rubber rollers top/bottom



#### Rails

Rails, 2.0 m, left and right



elumatec AG Pinacher Straße, 61 75417 Mühlacker Germany Tel +49 7041-14-184 sales@elumatec.com www.elumatec.com The right to make technical alterations is reserved.



## **TECHNICAL SHEET**

25/11/2025

### VR 3003 F / VERTICAL ROLLER CONVEYORS

- Length 3,000 mm
- Width 1,000 mm
- Height 2,490 mm
- Support rollers divided into three parts 3 x 120 mm
- Unit height 2,100 mm
- Load 200 kg
- Weight 180 kg